

EasyLift







Part M Compliant Platform Lift (certified to EN81-41)

EasyLift is an elegant platform lift which fits both external and indoor settings. This access solution has been designed by architects and features clean lines. It is suitable for both residential and commercial environments to provide access to areas where there is a small difference in level.



EasyLift

Features

Four battery run actuators at each corner Constant pressure controls Upper call station: hold to run (wireless) Lower call station: hold to run (wireless) (can be wall mounted or flush in wall) Automatic gate as standard Polycarbonate sides and gate

Optional Features

Key switch (school control) Remote control Remote alarm sounder Auto-dialler Safety glass (avilable on 1100mm wide platform) Vertical barrier on upper landing

Specifications

Drive Actuator system with brushless motor

Capacity 400kg Speed 0.15m/s

Travel 70mm - 1250mm

SPACE REQUIREMENT / FLOOR APERTURE

70mm (or 315mm ramp option available)

SIZES

Platform Space requirement in pit 800mm x 1400mm 1060 x 1520mm 900mm x 1400mm 1160 x 1520mm 1100mm x 1400mm 1360 x 1520mm

LIFTING PLATFORM

Finishes Akzo Nobel 900 Sable (standard grey)

> Any four digit RAL colour on request Standard - Grey Vinyl Anti-slip (internal)

Standard - Diamond plate (external)

DOORS

Flooring

Finishes Akzo Nobel 900 Sable (standard grey)

Any four digit RAL colour on request

ELECTRICAL DETAILS / POWER REQUIREMENT

Single phase 5 amp fused spur Supply

